

INTRODUCING THE BEST LINE OF SOLUTIONS IN
**GEOMEMBRANES
IN THE MARKET**

TechGeo PRO

Polithylene geomembrane (HDPE / LLDE)
International Standard Manufactured GRI GM-13
and GM17)

Tech Features:

- GRI GM 13 and GM17
- Lowest permeability
- Highest Chemical Resistance
- Highest Mechanical Resistance
- High Durability

Models:

Smooth - 23ft

Textured - 23ft

Thickness - 0.5mm to 2.5mm

TechGeo Innov

Polithylene geomembrane (HDPE / LLDE)
Developed under International Guidelines.
Designed less demanding projects Cost Benefit .

Tech Features:

- Latest generation resins
- Innovative productive system
- Affordable and lighter components
- High Mechanical and Chemical resistance that meets GRI GM 13 and GM 17 Standards.

Models:

Smooth - 19ft and 23ft

Thickness - 0.5mm to 2.5mm

TechGround Geosynthetics is one of the technology leaders, in engineering, environmental and agrobusiness solutions worldwide. Our company is staffed with world class engineers and a highly trained customer support team ready to assist your project from inception to completion.



contato@techground.com.br
www.techground.com.br

+55 11 2970 1610

 Tech Ground

 techgroundoficial

 oficialtechground



TechGeo

Durability

Polithylene geomembrane (HDPE / LLDE)
Premium product - Surpasses all standards of any
geomembrane in the market.

Tech Features:

- 40% more durable
- Designed for long lasting projects
- Transcends GRI GM 13 and GM 17 standards
- High Mechanical and Chemical resistance

Models:

Smooth - 23ft

Textured - 23ft

Thickness - 0.5mm to 2.5mm

EcoTech

Polithylene geomembrane (HDPE / LLDE)
Developed with high quality resins popularly used for
temporary and landscaping projects.

Tech Features:

- Colors available: Black/White, Black/Blue and Black/Green
- Low permeability
- Low dilation

Models:

Smooth - 19ft

Textured - 19ft

Thickness - 0.8mm to 2.5mm

ACCESSORIES GEO SUPPLIES

WELDING ROD



HDPE OR
LLDPE PROFILE

